

FFV SideKick HD HD-SDI Recorder



Display

4.3" color TFT display

Resolution

480 × 272 px

Digital Input

HD-SDI, HDMI

Digital Output

HD-SDI, HDMI

Standards

SMPT 274M (1080p: 29.97/25/23.98; 1080i:59.94/50)

Standards

SMPT 296M (720p: 59.94/50/29.97/25/23.98)

Connections

BNC 75 ohms, HDMI Type C Mini

Digital Audio Input/Output

8 channels embedded HD-SDI

Connections

BNC or HDMI unbalanced

Resolution

24 bits

Sampling rate

48 KHZ

Analog Input/mic

2 line level

Connection

3.5 mm

Resolution

16 bits

Audio out
3.5 mm stereo headphone jack

Drives

Maximum drive
1 (removable)
Supported drive
2.5 SATA SSD

Time code
Embedded
USB Port
For future use

Video Compression
Apple ProRes 422 ? standard, upgradable to ProRes 422 HQ
Max. Bit rate
145-220 Mbit/s

Power supply
12 VDC
Power connector
Mini XLR
Power requirement
9-16 V DC
Power consumption
Active record/playback: 21 W
Power Consumption
Record ready standby: 8W
Power Options
Anton Bauer or V-Mount battery, adapter cable external battery with charger option