



Large-scale screens no longer fear the “tensioning test”.

In addition to its trademark 150 mm diameter aluminium roller, and the case which is open underneath, the Alumax screen can count on another formidable feature to guarantee the perfect planarity of large-scale canvases: the CTS (Constant Tension System), which ensures the constant self-tensioning of the screen by means of two counterweights hooked onto hinges placed at the ends of the screen's base, devised for tensioning rigid cables threaded through lateral eyelets. This also prevents the formation of creases during rolling, since the eyelets are positioned outside the projection surface (see page 8).

The ideal technical solution for excellent projection even in the largest spaces.

Create your own screen with the PSS:

- > **personalized dimensions:** width and height
- > **roller type:** standard motorized
- > **case:** available only with case
- > **case color:** available in white or black
- > **projection surfaces:** ReferenceWhite, VisionWhite, VisionAcoustik and Vision MacroAcoustik only with black borders
- > **height of top:** from 10 to 20 cm
- > **projection surface drop:** front or rear
- > **side of command/motor:** right or left

Standard accessories:



- > kit with wall -or ceiling- quick mount brackets
- > unipolar selector switch

Optional accessories:

- > receiver and RF remote control for motorized screen (3 modalities: basic, automatic and compatible with domotic systems)
- > receiver and infrared remote control
- > bracket extensions for screens up to 60 cm



Format	Overall Width	Overall Height	Surface Width	Surface Height	Net Surface Width	Net Surface Height	Standard Top	Max Extra Top	Diagonal Inches	Shipment Sizes	Net Weight	Gross Weight
	A	E	F	G	H	I	P	cm	O	cm	kg	kg
4:3	512	385	474	363	464	348	10	20	228	530x29x32	82	107
	612	460	574	438	564	423	10	20	278	630x29x32	100	125
16:9	512	298	474	276	464	261	10	20	210	530x29x32	80	105
	612	354	574	332	564	317	10	20	255	630x29x32	98	123
16:10	512	327	474	305	464	290	10	20	215	530x29x32	80	105
	612	390	574	368	564	353	10	20	262	630x29x32	98	123
21:9	512	235	474	212	464	197	10	20	199	530x29x32	80	105
	612	277	574	255	564	240	10	20	241	630x29x32	98	123



Standard formats



4:3

PSS formats



21:9



21:9



16:9



16:10



5:4



1:1

Surfaces Fireproof Certification

